

Chain Wax Aerosol

Applications

Castrol Chain Wax is an advanced synthetic based motorcycle chain lubricant that sets a new standard in chain lubrication.

Castrol Chain Wax is suitable for all makes of on and off-road motorcycles. To achieve the maximum performance clean the chain properly with Castrol Chain Cleaner before applying Castrol Chain Wax.

Castrol Chain Wax is also suitable for "O" ring, non "O" ring and racing chains. Castrol Chain Wax should be applied according to manufacturers' instructions.

Features / Benefits

Castrol Chain Wax provides the following benefits:-

lubrication and protection for maximum power under arduous conditions adhesion for reduced fling protection against corrosion, rust and wear high temperature performance and low frictional properties resistance to water "wash off"

Specifications / Performance

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products. Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Units

Typical Characteristics

Test Methods

Value:

Test	Data
Appearance before dry	White to creamy white liquid
Appearance when dry	Tenacious medium soft wax
Wax protection IP50	110
Drop Point ºC IP133	118
Water Spray off ASTM D4049	2.6
Solvent %	30

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or

completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for anyloss or damage resulting from anyhazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/uk

Supplied By:

Gannon Oils Ltd., Unit 6 Sovereign Court, Poulton Business Park, Poulton-le-Fylde, Lancashire FY6 8JX.

Tel: 01253 899240 Fax: 01253 899280 www.gannonoils.com

