



**GANNON OILS LTD**  
9-11 WOOD STREET  
POULTON INDUSTRIAL EST.  
POULTON-LE-FYLDE  
LANCASHIRE  
FY6 8JY  
TEL: 01253 899240  
FAX: 01253 899280

# SPECIFICATION SHEET

## ACCESS GREASE

**Product Code: GR2080-2084**

### DESCRIPTION

Access Grease is a refined fully synthetic grease containing PTFE which lends itself for application to a wide range of industrial equipment particularly that operating in the **Access hire and Crane hire industry**.

### FEATURES

Superb mechanical stability  
Superb oxidation stability  
Superb anti-wear properties  
Superb resistance to shock  
Superb oil separation

### Excellent Boom Grease

Wide temperature range	:	-40°C to 350°C
High Technology	:	The latest formulation for excellent results
Economical	:	Small applications give good lubrication film
Fast Action	:	Penetrates in seconds
Clean Lubrication	:	Non staining lubrication film
Corrosion Protection	:	Effective on all metals
No Mineral Oil	:	Safe for use with expensive seals

Access Grease will resist hot, cold and salt water and will function effectively across a wide temperature band making it one of the most versatile and effective access & crane lubricants available today. The added sub-micron particle size PTFE gives excellent dry lubrication and forms a barrier between all surfaces.

### TYPICAL PHYSICAL CHARACTERISTICS

Density	:	0.98
Appearance	:	Translucent Grease
Penetration	:	280mm
Flash point	:	240°C
Drop point	:	None melting
Corrosion Test ASTM D-1743	:	Pass
Oxidisation @ 100 hours	:	0
Evaporation Loss ASTM D-972	:	<1%
Water Resistance after 500 hours	:	100%
Effect on Copper	:	None
Oil Separation	:	None