

Performance you can trust

SAPPHIRE® 2

Long life multi-purpose grease.

Designed for the effective lubrication and protection of all types of ball, roller and plain bearings.

Features

- Temperature range –30°C to 150°C
- Outstanding EP performance (>800kg weld load)
- Revolutionary multi-complex soap technology
- Greatly extended lubrication intervals
- typically 3 times longer than conventional soap thickened greases
- Good corrosion resistance
- Blue in colour for high visibility

Directions for Use

- Apply manually or with a suitable applicator e.g. ROCOL grease gun
- Compatible with other soap thickened greases. However, for best results, the previous lubricant should be removed prior to application.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Sapphire® 2

Appearance	Smooth, blue grease
Worked penetration	290-320
Base type	Severely refined mineral oil
Thickener	Multi-complex soap technology
Temperature range	-30°C to 150°C
Base fluid viscosity at 40°C	180 cSt
Base fluid viscosity at 100°C	17 cSt
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	>800 kg
Mean hertz load	120 kg
Timken 'OK' Load (IP 326)(ASTM D2509)	60lb
Copper Corrosion test (IP 112)(ASTM D130)	1a
Corrosion test - Emscor (IP 220)	0:0
Water Washout Test (IP 215)(ASTM D1264)	2%
Storage	Storage temperature should be controlled to between 1 and 40°C.
Pack sizes – Part Codes	400g – p/c 12171
	5kg – p/c 12176
	18kg – p/c 12175
	50kg – p/c 12178
	185kg – p/c 12179

T +44 (0) 113 232 2600
 F +44 (0) 113 232 2740
 E customer-service@rocol.com
 www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
 Certificate No. FM 12448



BS EN ISO 14001
 Certificate No. EMS 67596



OHSAS 18001
 Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.