



SPECIFICATION SHEET

AQUAJET 2

Aquajet 2 has been developed to exceed the latest NMMA standard (National Marine Manufacturers Association) to meet outboard manufacturers' performance requirements of TC-W3 for pre-mix direct oil injection, direct injection two cycle engines.

Aquajet 2 a non toxic marine lubricant, formulated with synthetic technology and the latest ashless additives that lead to clean burning characteristics with improved engine performance, reduced wear on engine components and extended engine life.

Aquajet 2 contains special ashless detergents designed to ensure high performance whilst efficiently cleaning the engine components to prevent piston rings from sticking, scuffing, deposits, whilst also preventing spark plug fouling and preignition problems.

BENEFITS

- Non toxic to marine life
- High performance
- Extended engine life
- No plug fouling or preignition
- Clean burning characteristics

APPLICATIONS

Aquajet 2 meets and exceeds manufacturer's recommendations for use in two cycle water cooled outboard engines that require TC-W3 quality outboard lubrication such as:

- Yamaha
- Mercury
- Bombardier
- Johnson
- Evinrude
- Nissan
- Suzuki
- Kawasaki
- OMC

TYPICAL TECHNICAL DATA

NMMA	:	TC-W3
API	:	TD
Appearance	:	Amber clear fluid
Odour	:	Bland
Specific Gravity @ 15.5°C	:	0.925
Kinematic Viscosity cSt @ 100°C	:	8.6
Flash Point (Closed) °C	:	120

Gannon Oils Ltd, Unit 6 Sovereign Court, Wyrefields, Poulton Business Park, Poulton-le-Fylde, Lancashire FY6 8JX
TEL: 01253 899240, FAX: 01253 899280, Email sales@gannonoils.com, www.gannonoils.com

Latest Up-date: 12/01/2010