



Product Data

Rustilo 181

Solvent based Rust Preventive

DESCRIPTION

Rustilo 181 is a dark brown solvent deposited rust preventive fluid which, after evaporation of the solvent, gives a hard waxy yet flexible film.

APPLICATION

Rustilo 181 is a long term protective for use in severe conditions where a high degree of protection is required. It is ideal for protection of certain engine spares such as fuel injector nozzles, fin tubes and similar highly finished parts prior to long-term storage or transportation.

Rustilo 181 used to be applied by immersion, brush or spray.

FEATURES

- ◆ Reliable corrosion protection
- ◆ Long bath-lifetimes possible
- ◆ Easy to apply
- ◆ Dries quickly

REMOVAL

If required protective films of Rustilo 181 can be removed by using a petroleum solvent or alkaline process cleaner, all available from Castrol.

TECHNICAL DATA

Appearance,			amber fluid
Relative Density @ 15°C,	kg/m ³	DIN 51 757	840 - 870
Flash Point,	°C	DIN 51 755	40
Viscosity @ 20°C,	mm ² /sec	DIN 51 562	65
Type of Film,			hard, waxy
Total Film Forming Content	%		50
Film Thickness	µm		20 - 40
Coverage	kg/100 m ²		7 - 10
Corrosion Protection,	years	Indoor storage	up to 8 - 10
	month	Outdoor storage*	12 - 24
Drying Time	min		60

* (assumes primary protection from the elements by tarpaulin or other form of cover)

Rustilo 181
14/04/2004

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the date of printing. It should be noted however that the information may be effected by changes subsequent to the date of printing in the blend formulation or methods of application of any of the products referred to or in the requirements of any specification approval relating to any such Products

Castrol International
Pipers Way
Swindon
SN3 1RE
United Kingdom
Tel +44 (0)1793 452111
Fax +44 (0)1703 486083